

SAFETY DATA SHEET

Version 6.1 Revision Date 02.07.2019 Print Date 04.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : (\pm) -MDMA solution

Product Number : M-013
Brand : Cerilliant
Index-No. : 603-001-00-X

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : MilliporeSigma Canada Ltd

2149 WINSTON PARK DRIVE

OAKVILLE ON L6H 6J8

CANADA

Telephone : +1 905 829-9500 Fax : +1 905 829-9292

1.4 Emergency telephone number

Emergency Phone # : 800-424-9300 CHEMTREC (USA)

+1-703-527-3887 CHEMTREC

(International)

24 Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with Hazardous Products Regulations (HPR) (SOR/2015-17)

Flammable liquids (Category 2), H225

Acute toxicity, Oral (Category 3), H301

Acute toxicity, Inhalation (Category 3), H331 Acute toxicity, Dermal (Category 3), H311

Specific target organ toxicity - single exposure (Category 1), H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Cerilliant - M-013 Page 1 of 10



Signal word	Danger
Hazard statement(s) H225 H301 + H311 + H331 H370	Highly flammable liquid and vapour. Toxic if swallowed, in contact with skin or if inhaled. Causes damage to organs.
Precautionary statement(s) P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 P240 P241 P242	Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting equipment. Use non-sparking tools.
P243 P260 P264	Take action to prevent static discharges. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling.
P270 P271 P280 P301 + P310 + P330	Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection. IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P303 + P361 + P353	Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P311	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor.
P308 + P311 P361 + P364	IF exposed or concerned: Call a POISON CENTER/doctor. Take off immediately all contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233 P403 + P235 P405 P501	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Molecular weight : 193.24 g/mol

Component		Classification	Concentration *
Methanol			
CAS-No.	67-56-1	Flam. Liq. 2; Acute Tox. 3;	>= 90 - <=
EC-No.	200-659-6	STOT SE 1; H225, H301,	100 %
Index-No.	603-001-00-X	H331, H311, H370	
Registration	01-2119433307-44-		
number	XXXX		
* Weight percent			

Cerilliant - M-013 Page 2 of 10



Methanol			
CAS-No.	67-56-1	Flam. Liq. 2; Acute Tox. 3;	>= 90 - <=
EC-No.	200-659-6	STOT SE 1; H225, H301,	100 %
Index-No.	603-001-00-X	H331, H311, H370	
Registration	01-2119433307-44-		
number	XXXX		
* Weight percent			

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

Cerilliant - M-013 Page 3 of 10



SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature -20 °C Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
Methanol	67-56-1	TWA	200 ppm 262 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Substance may be readily absorbed through intact skin			
		STEL	250 ppm 328 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
	Substance may be readily absorbed through intact skin			

Cerilliant - M-013 Page 4 of 10



		TWA	200 ppm	Canada. British Columbia OEL	
	Contributes	s significar	itly to the overall	exposure by the skin route.	
		STEL	250 ppm	Canada. British Columbia OEL	
	Contributes	Contributes significantly to the overall exposure by the skin route.			
		TWAEV	200 ppm 262 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants	
	Skin (percu	ıtaneous)			
		STEV	250 ppm 328 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants	
	Skin (percutaneous)				
		TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)	
		STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)	
Methanol	67-56-1	TWA	200 ppm 262 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)	
Remarks	Substance	Substance may be readily absorbed through intact skin		nrough intact skin	
		STEL	250 ppm 328 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)	
	Substance	Substance may be readily absorbed through intact skin		nrough intact skin	
		TWA	200 ppm	Canada. British Columbia OEL	
	Contributes significantly to the overall exposure by the skin route.				
		STEL	250 ppm	Canada. British Columbia OEL	
	Contributes	Contributes significantly to the overall exposure by the skin route.			
		TWAEV	200 ppm 262 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants	

Cerilliant - M-013 Page 5 of 10



Skin ((percutaneous)		
	STEV	250 ppm 328 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
Skin (Skin (percutaneous)		
	TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
	STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm Break through time: 30 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail

sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Cerilliant - M-013 Page 6 of 10



Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid
	0.1	

b) Odourc) Odour Thresholdd) pHNo data availableNo data available

e) Melting No data available point/freezing point

f) Initial boiling point and boiling range

64 - 65 °C 147 - 149 °F at 1.013 hPa

g) Flash point 9.7 °C (49.5 °F) - closed cup

h) Evaporation rate No data availablei) Flammability (solid, No data available gas)

j) Upper/lower Upper explosion limit: 36 %(V) flammability or explosive limits Upper explosion limit: 6 %(V)

k) Vapour pressure No data availablel) Vapour density No data available

m) Relative density 0.791 g/cm3 at 20 °C (68 °F)

n) Water solubility No data available
 o) Partition coefficient: No data available n-octanol/water

p) Auto-ignition No data available temperature

q) Decomposition No data available temperature

r) Viscosity No data availables) Explosive properties No data available

Cerilliant - M-013 Page 7 of 10

t) Oxidizing properties No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Acids, Oxidizing agents, Alkali metals, Strong oxidizing agents, Strong acids, Acid chlorides, Acid anhydrides, Reducing agents, Strong reducing agents, Phosphorus halides

10.6 Hazardous decomposition products

Other decomposition products - No data available Hazardous decomposition products formed under fire conditions. - Carbon oxides In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

Inhalation: No data available Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

Cerilliant - M-013 Page 8 of 10



ACGIH: No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by ACGIH.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

Methyl alcohol may be fatal or cause blindness if swallowed., Cannot be made non-poisonous., Effects due to ingestion may include:, Nausea, Headache, Vomiting, Gastrointestinal disturbance, Dizziness, Weakness, Confusion.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

Cerilliant - M-013 Page 9 of 10

SECTION 14: Transport information

DOT (US)

UN number: 1230 Class: 3 Packing group: II

Proper shipping name: MethanolSOLUTION

Reportable Quantity (RQ): Poison Inhalation Hazard: No

IMDG

UN number: 1230 Class: 3 (6.1) Packing group: II EMS-No: F-E, S-D

Proper shipping name: METHANOLSOLUTION

IATA

UN number: 1230 Class: 3 (6.1) Packing group: II

Proper shipping name: MethanolSOLUTION

SECTION 15: Regulatory information

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

SECTION 16: Other information

Further information

Copyright 2018 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.1 Revision Date: 02.07.2019 Print Date: 04.03.2022

Cerilliant - M-013 Page 10 of 10

