

SAFETY DATA SHEET

Version 5.8
 Revision Date 06/23/2015
 Print Date 03/20/2018

1. PRODUCT AND COMPANY IDENTIFICATION

Product name	: Acetic acid		
Product Number	: 242853		
Brand	: Sigma-Aldrich		
Product Use	: For laboratory research purposes.		
Supplier	: Sigma-Aldrich Canada Co. 2149 Winston Park Drive OAKVILLE ON L6H 6J8 CANADA	Manufacturer	: Sigma-Aldrich Corporation 3050 Spruce St. St. Louis, Missouri 63103 USA
Telephone	: +1 9058299500		
Fax	: +1 9058299292		
Emergency Phone # (For both supplier and manufacturer)	: +1-703-527-3887 (CHEMTREC)		
Preparation Information	: Sigma-Aldrich Corporation Product Safety - Americas Region 1-800-521-8956		

2. HAZARDS IDENTIFICATION

Emergency Overview

Target Organs

Teeth., KidneyTeeth., Kidney

WHMIS Classification

B3	Combustible Liquid	Combustible Liquid
E	Corrosive Material	Corrosive to skin

GHS Classification

Flammable liquids (Category 3)
 Acute toxicity, Oral (Category 5)
 Skin corrosion/irritation (Sub-category 1A)
 Serious eye damage/eye irritation (Category 1)

GHS Label elements, including precautionary statements

Pictogram



Signal word: Danger

Hazard statement(s)

H226	Flammable liquid and vapour.
H303	May be harmful if swallowed.
H314	Causes severe skin burns and eye damage.

Precautionary statement(s)

P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

HMIS Classification

Health hazard: 3
Chronic Health Hazard: *
Flammability: 2
Physical hazards: 0

Potential Health Effects

Inhalation May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract.
Skin May be harmful if absorbed through skin. Causes skin burns.
Eyes Causes eye burns. Causes severe eye burns.
Ingestion May be harmful if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : Glacial acetic acid
Formula : C₂H₄O₂
Molecular weight : 60.05 g/mol

CAS-No.	EC-No.	Index-No.	Concentration
Acetic acid			
64-19-7	200-580-7	607-002-00-6	<=100%

4. FIRST AID MEASURES**General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. FIREFIGHTING MEASURES**Conditions of flammability**

Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special protective equipment for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

Hazardous combustion products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Explosion data - sensitivity to mechanical impact

No data available

Explosion data - sensitivity to static discharge

No data available

Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Moisture sensitive.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
Acetic acid	64-19-7	TWA	10.000000 ppm 25.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		STEL	15.000000 ppm 37.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	10.000000 ppm	Canada. British Columbia OEL
		STEL	15.000000 ppm	Canada. British Columbia OEL
		TWAEV	10.000000 ppm 25.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		STEV	15.000000 ppm 37.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	10 ppm 25 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		STEL	15 ppm 37 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	10 ppm	Canada. British Columbia OEL
		STEL	15 ppm	Canada. British Columbia OEL
		TWAEV	10 ppm 25 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

		STEV	15 ppm 37 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	10.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	15.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	15 ppm	USA. ACGIH Threshold Limit Values (TLV)

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 480 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nature latex/chloroprene

Minimum layer thickness: 0.6 mm

Break through time: 32 min

Material tested: Lapren® (KCL 706 / Aldrich Z677558, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374
If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Eye protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Specific engineering controls

Use mechanical exhaust or laboratory fumehood to avoid exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form liquid

Colour colourless

Safety data

pH	2.4 at 60.05 g/l
Melting point/freezing point	Melting point/range: 16.2 °C (61.2 °F) - lit.
Boiling point	117 - 118 °C (243 - 244 °F) - lit.
Flash point	40.0 °C (104.0 °F) - closed cup
Ignition temperature	485 °C (905 °F)
Auto-ignition temperature	485.0 °C (905.0 °F)
Lower explosion limit	4 %(V)
Upper explosion limit	19.9 %(V)
Vapour pressure	73.3 hPa (55.0 mmHg) at 50.0 °C (122.0 °F) 15.2 hPa (11.4 mmHg) at 20.0 °C (68.0 °F)
Density	1.049 g/cm ³ at 25 °C (77 °F)
Water solubility	completely miscible
Partition coefficient: n-octanol/water	log Pow: -0.17
Relative vapour density	No data available
Odour	pungent
Odour Threshold	No data available
Evaporation rate	No data available

10. STABILITY AND REACTIVITY

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

No data available

Conditions to avoid

Heat, flames and sparks.

Materials to avoid

Oxidizing agents, Soluble carbonates and phosphates, Hydroxides, Metals, Peroxides, permanganates, e.g. potassium permanganate, Amines, Alcohols, Nitric acid

Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides
Other decomposition products - No data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Oral LD50

LD50 Oral - Rat - 3,310 mg/kg

Inhalation LC50

LC50 Inhalation - Mouse - 1 h - 5620 ppm

Remarks: Sense Organs and Special Senses (Nose, Eye, Ear, and Taste):Eye:Conjunctive irritation. Sense Organs and Special Senses (Nose, Eye, Ear, and Taste):Eye:Other. Blood:Other changes.

LC50 Inhalation - Rat - 4 h - 11.4 mg/l

Dermal LD50

LD50 Dermal - Rabbit - 1,112 mg/kg

Other information on acute toxicity

No data available

Skin corrosion/irritation

Skin - Rabbit - Causes severe burns.

Serious eye damage/eye irritation

Eyes - Rabbit - Corrosive to eyes

Respiratory or skin sensitisation

May cause sensitisation by skin contact.

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Reproductive toxicity

No data available

Teratogenicity

No data available

Specific target organ toxicity - single exposure (Globally Harmonized System)

No data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System)

No data available

Aspiration hazard

No data available

Potential health effects

Inhalation	May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract.
Ingestion	May be harmful if swallowed.
Skin	May be harmful if absorbed through skin. Causes skin burns.
Eyes	Causes eye burns. Causes severe eye burns.

Signs and Symptoms of Exposure

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, Ingestion or inhalation of concentrated acetic acid causes damage to tissues of the respiratory and digestive tracts. Symptoms include: hematemesis, bloody diarrhea, edema and/or perforation of the esophagus and pylorus, pancreatitis, hematuria, anuria, uremia, albuminuria, hemolysis, convulsions, bronchitis, pulmonary edema, pneumonia, cardiovascular collapse, shock, and death. Direct contact or exposure to high concentrations of vapor with skin or eyes can cause: erythema, blisters, tissue destruction with slow healing, skin blackening, hyperkeratosis, fissures, corneal erosion, opacification, iritis, conjunctivitis, and possible blindness., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects

No data available

Additional Information

RTECS: AF1225000

12. ECOLOGICAL INFORMATION**Toxicity**

Toxicity to fish semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) - > 1,000 mg/l - 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia EC50 - Daphnia magna (Water flea) - > 300.82 mg/l - 48 h
and other aquatic Method: OECD Test Guideline 202
invertebrates

Persistence and degradability

Biodegradability aerobic
Result: 99 % - Readily biodegradable
Remarks: Expected to be biodegradable

Bioaccumulative potential

No data available

Mobility in soil

No data available

PBT and vPvB assessment

No data available

Other adverse effects

Biochemical Oxygen 880 mg/g
Demand (BOD)

Additional ecological No data available
information

13. DISPOSAL CONSIDERATIONS**Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION**DOT (US)**

UN number: 2789 Class: 8 (3) Packing group: II
Proper shipping name: Acetic acid, glacial
Reportable Quantity (RQ): 5000 lbs
Marine pollutant: No
Poison Inhalation Hazard: No

IMDG

UN number: 2789 Class: 8 (3) Packing group: II EMS-No: F-E, S-C
Proper shipping name: ACETIC ACID, GLACIAL
Marine pollutant: No

IATA

UN number: 2789 Class: 8 (3) Packing group: II
Proper shipping name: Acetic acid, glacial

15. REGULATORY INFORMATION

WHMIS Classification

B3	Combustible Liquid	Combustible Liquid
E	Corrosive Material	Corrosive to skin

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

16. OTHER INFORMATION**Text of H-code(s) and R-phrase(s) mentioned in Section 3****Further information**

Copyright 2015 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.
